

# Safety Data Sheet

Material: JB 2619-002

SDS Up.Date Data (dd/mm/yyyy) : 09/04/2018

## 1. Product and company identification

### 1.1 Identification of the substance or preparation:

**Commercial product name:**

Use of substance / preparation

Industrial.  
Mold making

### 1.2 Company/undertaking identification:

Manufacturer/distributor:

Nolato Jabar LLC  
252 Brighton Road  
Andover, NJ 07821  
USA

Customer information:

InfoLine:  
Tel (973) 786-5000, Fax (973) 786-6067  
Hours of operation:  
Monday - Friday, 8:30 am to 5 pm (eastern standard time)

## 2. Hazards identification

### 2.1 Classification of the substance or mixture

**Classification (GHS):**

Not a hazardous substance or mixture.

### 2.2 Label elements

**Labelling (GHS):**

No labeling according to GHS required.

### 2.3 Other hazards

Product can release hydrogen. Risk of hydrogen gas formation with water, alcohols, acids, metallic salts, amines and alkalis. In combination with oxygen, the released hydrogen can form oxyhydrogen.

## 3. Composition/information on ingredients

### 3.1 Chemical characterization (preparation)

Chemical characteristics

Polydimethylsiloxane with hydrogen groups + Polydimethylsiloxane with vinyl groups and auxiliary

### 3.2 Information on ingredients:

Type	CAS No.	Substance	Content [wt. %]		Note
			Lower	Upper	
INHA	14808-60-7	Quartz	35.0	<=40.0	C1, C2
INHA	13463-67-7	Titanium dioxide	0.1	<=1.0	C1

**Type:** HYD - by-product upon hydrolysis, INHA - ingredient, NEBE - by-product, MONO - residual monomer, VERU - impurity, VUL - by-product upon vulcanization. \*\*\* **Note:** C1 - IARC carcinogen, C2 - NTP carcinogen, C3 - OSHA carcinogen, NH - non-hazardous, R - reproductive toxin.

Quartz: This component does not impact the product's hazard classification. Due to the product's physical properties, particulate inhalation exposure is not possible. Titanium dioxide: This component does not impact the product's hazard classification. Due to the product's physical properties, particulate inhalation exposure is not possible.

# Safety Data Sheet

Material: JB 2619-002

Substances listed in the Subsections "HAPS" and "California Proposition 65 Carcinogens / Reproductive Toxins" that are not listed in this section are only present at quantities below 0.1% for California Proposition 65 listed toxins or below 1% for non-carcinogenic HAPS or they are inextricably bound in the product. Specific chemical identities and/or exact percentage (concentration) of the composition may have been withheld as a trade secret.

## 4. First-aid measures

### 4.1 General information:

Get medical attention if irritation or other symptoms occur. Before seeking medical attention remove contaminated clothing and shoes. Take a copy of the Safety Data Sheet when going for medical treatment.

### 4.2 After inhalation

No special treatment required.

### 4.3 After contact with the skin

For skin contact, immediately wipe away excess material. Use a waterless hand cleaner to remove as much of the remaining material as possible. Wash with soap and water.

### 4.4 After contact with the eyes

If contact with eyes, immediately hold eyelids apart and flush with plenty of water for at least 15 min.

### 4.5 After swallowing

No special treatment required.

### 4.6 Advice for the physician

Treat symptomatically.

## 5. Fire-fighting measures

### 5.1 Flammable properties:

Property:	Value:	Method:
Flash point.....	> 200 °C (> 392 °F)	(ASTM D3278, DIN 55680, ISO 3679)
Boiling point / boiling range .....	> 200 °C (> 392 °F)	
Lower explosion limit (LEL) .....	not applicable	
Upper explosion limit (UEL).....	not applicable	
Ignition temperature .....	not determined	

### 5.2 Fire and explosion hazards:

Caution! Under certain conditions this material may generate flammable hydrogen gas. Consider possible formation of explosive mixtures with air, for example in uncleaned containers by moisture. Never use welding or cutting torch on or near any container of this material, even if empty, because an explosion could occur. Spontaneous ignition is possible due to electrostatic discharge. The generation of hydrogen gas is increased under circumstances mentioned in Sect. 10 "Stability and reactivity". Explosion limits for hydrolysis product: 4-75.6% v/v (hydrogen) .

### 5.3 Recommended extinguishing media:

carbon dioxide , dry sand , alcohol-resistant foam .

### 5.4 Unsuitable extinguishing media:

water , dry chemical , halones .

### 5.5 Special exposure hazards arising from the substance or preparation itself, combustion products, resulting gases

Hazardous decomposition products: carbon dioxide , carbon monoxide , formaldehyde , silicon dioxide and incompletely burnt hydrocarbons .

### 5.6 Fire fighting procedures:

Fire fighters should wear full protective clothing including a self-contained breathing apparatus. Cool endangered containers with water. Hydrogen gas can become trapped under foam blankets, so sources of ignition must be eliminated during the clean-up and recovery process.

# Safety Data Sheet

Material: JB 2619-002

## 6. Accidental release measures

### 6.1 Precautions:

Secure the area. Wear personal protection equipment (see section 8). Keep unprotected persons away. If material is released indicate risk of slipping. Do not walk through spilled material.

**HAZWOPER PPE Level:** D

### 6.2 Containment:

Prevent material from entering surface waters, drains or sewers and soil. Close leak if possible without risk. Retain contaminated water/extinguishing water. Dispose of in prescribed marked containers. Inform authorities if substance leaks into surface waters, sewerage or ground.

Spills of material which could reach surface waters must be reported to the United States Coast Guard National Response Center's toll free phone number (800) 424-8802.

### 6.3 Methods for cleaning up

Scoop up large quantities after dusting surfaces with sand or Fuller's earth to prevent sticking. Sweep or scrape up the spilled material and place in an appropriate chemical waste container. Clean any slippery coating that remains using a detergent / soap solution or another biodegradable cleaner. Apply sand or other inert granular material to improve traction.

### 6.4 Further information:

Exhaust vapours. Eliminate all sources of ignition. Consider explosion protection. Material designated for disposal must be segregated from incompatible substances or materials specified in Sect. 10. Do not blend contaminated material with uncontaminated material. Do not seal collecting vessel gas-tight. Observe notes under section 7.

## 7. Handling and storage

### 7.1 Handling

#### Precautions for safe handling:

Ensure adequate ventilation. Open and handle container with care. Keep container closed when not in use. Keep away from incompatible substances in accordance with section 10. Where possible, inert process equipment and blanket vessels, tanks and containers with nitrogen to reduce the available oxygen level. Contact WACKER for additional publications on the safe Handling of SiH Products. Observe information in section 8.

#### Precautions against fire and explosion:

Product can release hydrogen. Flammable vapors may accumulate and form explosive mixtures with air in containers, process vessels, including partial, empty and uncleaned containers and vessels, or other enclosed spaces. Keep away from sources of ignition and do not smoke. Take precautionary measures against electrostatic charging. Cool endangered containers with water.

### 7.2 Storage

#### Conditions for storage rooms and vessels:

Do not store in virgin glass containers with basic surface. Observe local/state/federal regulations.

#### Advice for storage of incompatible materials:

Do not store with: basic substances (e.g. alkalis, ammonia, amines), oxidizing agents, strong acids. Observe local/state/federal regulations.

#### Further information for storage:

Store in a dry and cool place. Protect against moisture. Store container in a well ventilated place.

**Maximum temperature allowed during storage and transportation:** 32 °C (89 °F)

Temperature limit based on safety considerations.

## 8. Exposure controls and personal protection

### 8.1 Engineering controls

#### Ventilation:

Use only with adequate ventilation.

#### Local exhaust:

Local exhaust ventilation which meets the requirements of ANSI Z9.2 is recommended to control airborne contaminants at the point of use.

# Safety Data Sheet

Material: JB 2619-002

## 8.2 Associate substances with specific control parameters such as limit values

| not applicable

## 8.3 Personal protection equipment (PPE)

### Respiratory protection:

Respiratory protection is not normally required.

### Hand protection:

butyl rubber protective gloves , neoprene gloves , PVC gloves .

### Eye protection:

Safety glasses with side shields or chemical safety goggles.

### Other protective clothing or equipment:

Additional protective clothing or equipment is not normally required. Provide eye bath and safety shower.

## 8.4 General hygiene and protection measures:

Avoid contact with eyes, skin and clothing. When handling do not eat, drink, smoke or apply cosmetics. Follow standard industrial hygiene practices when using this material. Wash thoroughly after handling.

## 9. Physical and chemical properties

### 9.1 Appearance

Physical state / form .....: liquid - viscous  
Colour .....: grey  
Odour .....: slight

### 9.2 Safety parameters

Property:	Value:	Method:
Melting point / melting range .....	not applicable	
Boiling point / boiling range .....	> 200 °C (> 392 °F)	
Flash point.....	> 200 °C (> 392 °F)	(ASTM D3278, DIN 55680, ISO 3679)
Ignition temperature .....	not determined	
Lower explosion limit (LEL) .....	not applicable	
Upper explosion limit (UEL).....	not applicable	
Vapour pressure.....	not applicable	
Density .....	1.42 g/cm <sup>3</sup>	
Water solubility / miscibility.....	virtually insoluble	
pH-Value .....	not applicable	
Viscosity (dynamic) .....	40000 mPa.s	

### 9.3 Further information

According to previous experience autoignition of SiH containing products on a catalytically active surface may occur at a much lower temperature than expected. This applies to porous or fibrous substances including those with alkaline surfaces, such as thermal insulation and cementaceous insulating materials. Explosion limits for released hydrogen: 4 - 75.6%(V). pH Value: Product displays neutral reaction.

| Odour limit.....: no data available  
Percent Volatiles.....: 1.15 %  
Corrosive to Steel or Aluminum.....: Not corrosive to steel or aluminum.

## 10. Stability and reactivity

### 10.1 General information:

| If stored and handled in accordance with standard industrial practices no hazardous reactions are known.

### 10.2 Conditions to avoid

| moisture , Heat, open flames, and other sources of ignition. Contact with contaminated piping or vessels or with corroded and rusty containers can increase the rate of hydrogen formation. Observe information in section 7.

# Safety Data Sheet

Material: JB 2619-002

## 10.3 Materials to avoid

proton-active substances . Reacts with: acids , basic substances (e.g. alkalis, ammonia, amines) . alcohols , water , moisture , oxidizing agents , catalyst . Reaction causes the formation of: hydrogen .

## 10.4 Hazardous decomposition products

Upon contact with the substances mentioned in 10. hydrogen . Measurements have shown the formation of small amounts of formaldehyde at temperatures above about 150 °C (302 °F) through oxidation.

## 10.5 Further information:

Hazardous polymerization cannot occur.

## 11. Toxicological information

### 11.1 Information on toxicological effects

#### 11.1.1 Further toxicological information

Quartz has been classified by IARC as carcinogen group 1 ("carcinogenic to humans") and by NTP as known to be a human carcinogen. Titanium dioxide has been classified by IARC as carcinogen group 2B ("possibly carcinogenic to humans"). No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

## 12. Ecological information

### 12.1 Additional information

According to our present knowledge no data known.

## 13. Disposal considerations

### 13.1 Product disposal

Recommendation:

Risk of oxyhydrogen formation upon contact with the substances mentioned in 10. Material designated for disposal must be segregated from incompatible substances or materials specified in Sect. 10. Wastes of this material should not be mixed with other wastes. Provide measures such as vented bungs to ensure pressure relief in the waste containers. Material that cannot be used, reprocessed or recycled should be disposed of in accordance with Federal, State, and local regulations at an approved facility. Depending on the regulations, waste treatment methods may include, e.g., landfill or incineration.

### 13.2 Packaging disposal

Recommendation:

Containers may contain hazardous quantities of hydrogen gas. Uncleaned containers should not be reused to hold another material due to the potential for reaction between residual product and incompatible materials. Completely discharge containers (no tear drops, no powder rest, scraped carefully). Containers may be recycled or re-used. Observe local/state/federal regulations. Uncleaned packaging should be treated with the same precautions as the material.

## 14. Transport information

### 14.1 US DOT & CANADA TDG SURFACE

Valuation .....: Not regulated for transport

### 14.2 Transport by sea IMDG-Code

Valuation .....: Not regulated for transport

### 14.3 Air transport ICAO-TI/IATA-DGR

Valuation .....: Not regulated for transport

## 15. Regulatory information

# Safety Data Sheet

Material: JB 2619-002

## 15.1 U.S. Federal regulations

### TSCA inventory status and TSCA information:

This material or its components are listed on or are in compliance with the requirements of the TSCA Chemical Substance Inventory.

### TSCA 12(b) Export Notification:

This material does not contain reportable amounts of any TSCA 12(b) listed chemicals.

### CERCLA Regulated Chemicals:

This material does not contain any CERCLA regulated chemicals.

### SARA 302 EHS Chemicals:

This material does not contain any SARA extremely hazardous substances.

### SARA 311/312 Hazard Class:

This product does not present any SARA 311/312 hazards.

### SARA 313 Chemicals:

This material does not contain any SARA 313 chemicals above de minimus levels.

### HAPS (Hazardous Air Pollutants):

CAS No.	Chemical	Upper limit wt. %
108-88-3	Toluene	<=0.0110

## 15.2 U.S. State regulations

### California Proposition 65 (Safe Drinking Water and Toxic Enforcement Act of 1986):

California Proposition 65 Carcinogens:

14808-60-7	Quartz
13463-67-7	Titanium dioxide
1333-86-4	Carbon black

California Proposition 65 Reproductive Toxins:

108-88-3	Toluene
----------	---------

### Massachusetts Substance List:

13463-67-7	Titanium dioxide
14808-60-7	Quartz

### New Jersey Right-to-Know Hazardous Substance List:

13463-67-7	Titanium dioxide
14808-60-7	Quartz

### Pennsylvania Right-to-Know Hazardous Substance List:

13463-67-7	Titanium dioxide
14808-60-7	Quartz

## 15.3 Details of international registration status

Relevant information about individual substance inventories, where available, is given below.

People's Republic of China .....	: <b>IECSC</b> (Inventory of Existing Chemical Substances in China): This product is listed in, or complies with, the substance inventory.
United States of America (USA).....	: <b>TSCA</b> (Toxic Substance Control Act Chemical Substance Inventory): All components of this product are listed as active or are in compliance with the substance inventory.
Philippines.....	: <b>PICCS</b> (Philippine Inventory of Chemicals and Chemical Substances): This product is listed in, or complies with, the substance inventory.
Japan .....	: <b>ENCS</b> (Handbook of Existing and New Chemical Substances): This product is not listed or in compliance with the substance inventory.
Australia .....	: <b>AICS</b> (Australian Inventory of Chemical Substances): This product is listed in, or complies with, the substance inventory.

# Safety Data Sheet

Material: JB 2619-002

Taiwan (Republic of China)..... : **TCSI** (Taiwan Chemical Substance Inventory):  
This product is listed in, or complies with, the substance inventory. General note:  
The Taiwanese chemicals regulation requires a phase 1 registration for TCSI-listed  
or TCSI-compliant substances if imports to Taiwan or manufacturing in Taiwan  
exceed the trigger quantity of 100 kg/a (for mixtures to be calculated per each  
ingredient). It is the duty of the importing/manufacturing legal entity to take care of  
this obligation.

European Economic Area (EEA)..... : **REACH** (Regulation (EC) No 1907/2006):  
General note: the registration obligations for substances imported into the EEA or  
manufactured within the EEA by the supplier mentioned in section 1 are fulfilled by  
the said supplier. The registration obligations for substances imported into the EEA  
by customers or other downstream users must be fulfilled by the latter.

## 16. Other information

### 16.1 Additional information:

This Safety Data Sheet (SDS) meets the requirements of the Federal OSHA Hazard Communication Standard (29 CFR 1910.1200). This information relates to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is to the best of our knowledge and belief accurate and reliable as of the date compiled. However, no representation, warranty or guarantee expressed or implied, is made as to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability and completeness of such information for his own particular use. We do not accept liability for any loss or damage that may occur from the use of this information. Nothing herein shall be construed as a recommendation for uses which infringe valid patents or as extending a license under valid patents. This SDS provides selected regulatory information on this product, including its components. This is not intended to include all regulations. It is the responsibility of the user to know and comply with all applicable rules, regulations and laws relating to the product being used.

Vertical lines in the left-hand margin indicate changes compared with the previous version.

All deliveries are subject to the WACKER SILICONES Health Care Policy, which is available at [www.wacker.com](http://www.wacker.com).

### 16.2 Glossary of Terms:

ACGIH - American Conference of Governmental Industrial Hygienists	ppm - Parts per Million
DOT - Department of Transportation	SARA - Superfund Amendments and Reauthorization Act
hPa - Hectopascals	STEL - Short Term Exposure Limit
mPa*s - Milli Pascal-Seconds	TSCA - Toxic Substances Control Act
OSHA - Occupational Safety and Health Administration	TWA - Time Weighted Average
PEL - Permissible Exposure Limit	WHMIS - Canadian Workplace Hazardous Materials Identification System

Flash point determination methods	Common name
ASTM D56.....	Tagliabue (Tag) closed cup
ASTM D92, DIN 51376, ISO 2592 .....	Cleveland open cup
ASTM D93, DIN 51758, ISO 2719 .....	Pensky-Martens closed cup
ASTM D3278, DIN 55680, ISO 3679 .....	Setaflash or Rapid closed cup
DIN 51755.....	Abel-Pensky closed cup

### 16.3 Conversion table:

Pressure:..... : 1 hPa \* 0.75 = 1 mm Hg = 1 torr; 1 bar = 1000 hPa  
Viscosity:..... : 1 mPa\*s = 1 centipoise (cP)