

SAFETY DATA SHEET**SECTION 1 : IDENTIFICATION****Product Identifier :**

Medium Density Silicone Sponge Flame Retardant

Product Code(s) :

0202M FR

Product Use :

Mechanical Elastomer applications

Chemical Family :

Methylvinyl Siloxane

Supplier's Name and Address :Nolato Jabar LLC PO Box
1249 252 Brighton Road
Andover, NJ, USA 07821**Manufacturer's Name and Address :**

Refer to Supplier

Information Telephone # :

(973) 786-5000

24 Hr. Emergency Tel # :

(973) 786-5000

SECTION 2 : HAZARDS IDENTIFICATION**Emergency Overview****Fabrication Cautions !**

Dust created from cutting and/or grinding may cause eye and skin irritation and may also be harmful if inhaled.

Dust may also cause respiratory irritation and could result in pulmonary edema (fluid accumulation). May be harmful or fatal if swallowed. May cause gastrointestinal irritation. This material is not a potential aspiration hazard as provided.

This material is a cured elastomeric rubber posing no hazard when used for intended purpose.

POTENTIAL HEALTH EFFECTS :**Signs and symptoms of short-term (acute) exposure**

Skin

No toxic effects expected.

Eyes

No toxic effects expected.

Ingestion

Amounts transferred to the mouth by fingers, etc., during normal operations should not cause injury.

Effects of long-term (chronic) exposure

No known adverse chronic health effects, but unnecessary exposure to any chemical should be avoided.

Classification of the product

No need for classification according to GHS for this product.

Product does not require a hazard warning label.

Carcinogenic status : See TOXICOLOGICAL INFORMATION, Section 11.**Additional health hazards : See TOXICOLOGICAL INFORMATION, Section 11.****Potential environmental effects : See ECOLOGICAL INFORMATION, Section 12.****SECTION 3 : COMPOSITION / INFORMATION ON INGREDIENTS**

Ingredients	CAS #	Wt %
Silica, Amorphous	7631-86-9	>5
Silica, Quartz	14808-60-7	1-4
Dimethyl, Methyl Hydrogen Siloxane Copolymer	68037-59-2	1-4
Polydimethyl, Methylvinyl Siloxane Di-me Terminated	68083-18-1	>40
OBSH	80-51-3	2-5
Polysiloxane with functional groups + Filler + Auxiliary + Pigment		>5

SECTION 4 : FIRST AID MEASURES

First Aid : Eyes

If contact with eyes, immediately hold eyelids apart and flush with plenty of water for at least 15 min.

First Aid : Skin

Remove/Take off all contaminated clothing. Wash off immediately with soap and plenty of water. When symptoms persist or in all cases of doubt seek medical advice. Wash contaminated clothing before re-use.

First Aid : Ingestion

Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Seek immediate medical attention/advice. If vomiting occurs spontaneously, keep victim's head lowered (forward) to reduce the risk of aspiration.

First Aid : Inhalation

If breathed in, move person into fresh air. If breathing is irregular or stopped, administer artificial respiration. If breathing is difficult, give oxygen by qualified medical personnel only. When symptoms persist or in all cases of doubt seek medical advice.

Notes For Physician :

Treat Symptomatically

SECTION 5 : FIRE FIGHTING MEASURES

Fire Hazards/Conditions of Flammability

Not flammable under normal conditions of use. However, may ignite if exposed to extreme heat and flame. Closed containers may rupture if exposed to excess heat or flame due to a build-up of internal pressure

Flammability Classification (OSHA 29 CFR 1910.1200)

Not Flammable

Oxidizing Properties

None Known

Explosion Data; Sensitivity to Mechanical Impact/Static Discharge

Avoid dust cloud formation. Finely divided dust clouds may be sensitive to static discharge and pose a dust explosion hazard. Not expected to be sensitive to mechanical impact.

Suitable Extinguishing Media

Use media suitable to the surrounding fire such as water fog or fine spray, alcohol foams, carbon dioxide and dry chemical.

Special Fire-Fighting Procedures/Equipment

Move containers from fire area if safe to do so. Cool closed containers exposed to fire with water spray. Do not allow run-off from fire fighting to enter drains or water courses.

Hazardous combustion products

Carbon oxides; formaldehyde; silicon oxides; irritating fumes and smoke.

SECTION 6 : ACCIDENTAL RELEASE MEASURES

The following recommendations are established general accepted practices of containment, not specific to this material.

Personal Precautions

Restrict access to area until completion of clean-up. Ensure clean-up is conducted by trained personnel only. All persons dealing with clean-up should wear the appropriate protective equipment including self-contained breathing apparatus. Refer to Section 8, EXPOSURE CONTROLS AND PERSONAL PROTECTION, for additional information on acceptable personal protective equipment.

Environmental Precautions

Ensure spilled product does not enter drains, sewers, waterways, or confined spaces. If necessary, dike well ahead of the spill to prevent runoff into drains, sewers, or any natural waterway of drinking supply.

Spill Response/Cleanup

Remove all sources of ignition. Ventilate area of release. Stop the spill at source if it is safe to do so. Do not flush into surface water or sanitary sewer system. Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see Section 13). Avoid dust formation. Contaminated absorbent material may pose the same hazards as the spilled product. Notify the appropriate authorities as required.

Prohibited Materials

None known.

Special Spill Response Procedures

If a spill/release in excess of the EPA reportable quantity is made into the environment, immediately notify the national response center in the United States (phone: 1-800-424-8002).

SECTION 7 : HANDLING AND STORAGE**Safe Handling Procedures**

Use only in well-ventilated areas. Wear suitable gloves and eye/face protection. Avoid dust formation. Avoid breathing dust/fume/gas/mist/vapours/spray. Avoid contact with skin, eyes and clothing. Keep away from heat. Protect from moisture. Keep container tightly closed. Empty containers retain residue (liquid and/or vapour) and can be dangerous. Wash thoroughly after handling.

Storage Requirements

Keep containers tightly closed in a cool, well ventilated place. Keep away from heat. Inspect periodically for damage or leaks. Protect against physical damage. Keep containers dry and tightly closed to avoid moisture absorption and contamination.

SECTION 8 : EXPOSURE CONTROLS AND PERSONAL PROTECTION

This material is a cured elastomeric rubber posing no hazard when used for intended purpose.

Fabrication Cautions !

Dust created from cutting and/or grinding may cause eye and skin irritation and may also be harmful if inhaled. Dust may also cause respiratory irritation and could result in pulmonary edema (fluid accumulation). May be harmful or fatal if swallowed. May cause gastrointestinal irritation. This material is not a potential aspiration hazard as provided.

The following recommendations are established general accepted practices of containment, not specific to this material.

Ventilation and Engineering Measures

Use only in well-ventilated areas. Apply technical measures to comply with the occupational exposure limits. Where reasonably practicable, this should be achieved by the use of local exhaust ventilation and good general extraction. In case of insufficient ventilation, wear suitable respiratory equipment.

Respiratory Protection

In the case of vapour formation use a respirator with an approved filter. The filter class for the respirator must be suitable for the maximum expected contaminant concentration (gas/vapour/aerosol/particulates) that may arise when handling the product. If this concentration is exceeded, a self-contained breathing apparatus must be used.

Skin Protection

Impervious gloves must be worn when using this product. Advice should be sought from glove suppliers.

Eye/Face Protection

Chemical safety glasses with side shields or splash proof goggles.

Other Protective Equipment

Chemical resistant apron. Safety boots per regulations. Ensure that eyewash stations and safety showers are close to the workstation location.

General Hygiene Considerations

Avoid breathing dust/fume/gas/mist/vapours/spray. Avoid contact with skin, eyes and clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Remove and wash contaminated clothing before re-use.

SECTION 9 : PHYSICAL AND CHEMICAL PROPERTIES

Physical State	: Sponge	Appearance	: Gum
Odour	: Characteristic Odor	Odour Threshold	: N/Av
Physical State	: N/Av	Specific Gravity	: < 2
Boiling Point:	: N/Av	Coefficient of Water/Oil Distribution	: N/Av
Melting/Freezing Point	: N/Av	Solubility in Water	: Negligible
Vapour Pressure (mmHg@20°C/68°F)	: N/Av	Evaporation Rate (n-Butyl acetate = 1)	: N/Av
Vapour Density (Air=1)	: N/Av	Volatiles (% by weight)	: N/Av
Volatile Organic Compounds (VOC's)	: N/Av	Auto-ignition Temperature	: N/Av
Flash Point	: N/Av	Upper Flammable Limit (% by vol)	: N/Av
Flash Point Method	: N/Av	Flashback Observed	: N/Av
Lower Flammable Limit (% by vol.)	: N/Av		
Flame Projection Length	: N/Av		

SECTION 10 : STABILITY AND REACTIVITY
Chemical Stability

Stable under normal conditions.

Hazardous Reaction Potential

Will not occur.

Conditions to Avoid

Direct sources of heat.

Materials to Avoid and Incompatibility

Incompatible materials (see Section 7).

Hazardous Decomposition Products

None known, refer to hazardous combustion products in Section 5.

SECTION 11 : TOXICOLOGICAL INFORMATION
Target organs

Eyes, skin, respiratory system and digestive system.

Routes of Exposure

Inhalation : No *Skin Absorption* : No *Skin & Eyes* : YES *Ingestion* : YES

Carcinogenic Status

Avoid heating, which will result in the liberation of formaldehyde.

Reproductive Effects

Contains no ingredient listed as toxic to reproduction.

Mutagenicity

Contains no ingredient listed as a mutagen.

Epidemiology

Not available.

Sensitization to Material

Some fabrication processes may cause sensitization by skin contact.

Synergistic Materials

Not available.

Irritancy

May cause eye, skin and respiratory tract irritation.

Conditions Aggravated by Overexposure

Pre-existing skin, eye and respiratory disorders.

Medium Density Silicone Sponge Flame Retardant

0202M FR

SECTION 12 : ECOLOGICAL INFORMATION

Ecotoxicity :

No data is available on the product itself. The product should not be allowed to enter drains or water courses, or be deposited where it can affect ground or surface waters.

Mobility :

The product itself has not been tested.

Persistence :

The product itself has not been tested.

Bioaccumulation Potential :

The product itself has not been tested.

Other Adverse Environmental Effects :

None known.

SECTION 13 : DISPOSAL CONSIDERATIONS

Handling for Disposal :

Handle waste according to recommendations in Section 7.

Methods of Disposal :

Dispose in accordance with all applicable federal, state, provincial and local regulations. Contact your local, state, provincial or federal environmental agency for specific rules.

RCRA :

If this product, as supplied, becomes a waste in the United States, it may meet the criteria of a hazardous waste as defined under RCRA, Title 40 CFR 261. It is the responsibility of the waste generator to determine the proper waste identification and disposal method. For disposal of unused or waste material, check with local, state and federal environmental agencies.

SECTION 14 : TRANSPORT INFORMATION

Regulatory Information	UN Number	Shipping Name	Class	Packing Group	Label
49CFR/DOT	None	Not Regulated	Not Regulated	None	☒
49CFR/DOT Additional information	None	Not Regulated	Not Regulated	None	
TDG	None	Not Regulated	Not Regulated	None	☒
TDG Additional Information	None	Not Regulated	Not Regulated	None	

SECTION 15 : REGULATORY INFORMATION

US Federal Information :

TSCA: All listed ingredients appear on the Toxic Substances Control Act (TSCA) inventory.

CERCLA Reportable Quantity (RQ) (40 CFR 117.302): See Section 6 **SARA TITLE III:** Sec. 302, Extremely Hazardous Substances, 40 CFR 355: No Extremely Hazardous Substances are present in this material.

SARA TITLE III: Sec. 311 and 312, MSDS Requirements, 40 CFR 370 Hazard Classes: Immediate (Acute) health hazard; Chronic Health Hazard. Under SARA Sections 311 and 312, the EPA has established threshold quantities for the reporting of hazardous chemicals. The current thresholds are 500 pounds for the threshold planning quantity (TPQ), whichever is lower, for extremely hazardous substances and 10,000 pounds for all other hazardous chemicals.

SARA TITLE III: Sec. 313, Toxic Chemicals Notification, 40 CFR 372: This product may be subject to SARA notification requirements, since it contains Toxic Chemical constituents above their de minimus concentrations.

US State Right to Know Laws :

California Proposition 65: To the best of our knowledge, this product does not contain any chemicals known to the State of California to cause cancer or reproductive harm.

International Information :

Canadian Environmental Protection Act (CEPA) information: All ingredients listed appear on the Domestic Substances List (DSL).

WHMIS information :

This product has been classified according to the hazard criteria of the CPR and the SDS contains all of the information required by the CPR.

SECTION 16 : OTHER INFORMATION

HMIS Rating

* - Chronic Hazard 0 - Minimal 1 - Slight 2 - Moderate 3 - Serious 4 - Severe

Health : *1

Flammability : 1

Reactivity : 0

Legend :

ACGIH: American Conference of Governmental Industrial Hygienists
CA: California
CAS: Chemical Abstract Services
CERCLA: Comprehensive Environmental Response, Compensation, and Liability Act of 1980
CFR: Code of Federal Regulations
DOT: Department of Transportation
EPA: Environmental Protection Agency
HMIS: Hazardous Materials Identification System
HSDB: Hazardous Substances Data Bank
IARC: International Agency for Research on Cancer
Inh: Inhalation
N/Ap: Not Applicable
N/Av: Not Available
NFPA: National Fire Protection Association
NIOSH: National Institute of Occupational Safety and Health
NTP: National Toxicology Program

SDS Preparation Data (dd/mm/yyyy) : 09/07/2015

OSHA: Occupational Safety and Health Administration
PEL: Permissible Exposure Limit
RCRA: Resource Conservation and Recovery Act
RTECS: Registry of Toxic Effects of Chemical Substances
SARA: Superfund Amendments and Reauthorization Act
STEL: Short Term Exposure Limit
TDG: Canadian Transportation of Dangerous Goods Act & Regulations
TLV: Threshold Limit Values
TPQ: Threshold Planning Quantity
TSCA: Toxic Substance Control Act
TWA: Time Weighted Average
WHMIS: Workplace Hazardous Materials Identification System

References :

1. ACGIH, Threshold Limit Values and Biological Exposure Indices
2. International Agency for Research on Cancer Monographs, searched
3. Canadian Centre for Occupational Health and Safety, CInfoWeb databases, 2009 (Chempendium, HSDB and RTECs)
4. Safety Data Sheets from manufacturer
5. US EPA Title III List of Lists
6. California Proposition 65 List

Prepared for :

Prepared for :
Nolato Jabar LLC
252 Brighton Road Andover, NJ, USA 07821
Telephone: (973) 786-5000
Direct all enquiries to: Nolato Jabar LLC

**DISCLAIMER OF LIABILITY**

The information in the Safety Data Sheet is offered for your consideration and guidance when exposed to this product. Nolato Jabar LLC disclaims all expressed or implied warranties and assumes no responsibilities for the accuracy or completeness of the data contained herein. This Safety Data Sheet may not be changed, or altered in any way without the expressed knowledge and permission of Nolato Jabar LLC.

END OF DOCUMENT